

# DP-MS SLOW THINNER

Revision nr. 1  
Dated 09/06/2007  
Printed on 09/06/2007  
Page n.1 / 6

## Safety Data Sheet

### 1. Identification of the substance / preparation and the Company

#### 1.1 Identification of the substance or preparation

Product name DP-MS SLOW THINNER  
Intended use PAD PRINTING THINNER

#### 1.3 Company identification

Name Inkcups Now  
Full address 20 Locust Street Danvers MA. 01923  
District and Country USA

Phone 978-646-8980  
Fax 978-646-8981  
Emergency Telephone Number Cemtrek 800-424-9300

### 2. Composition / Information on ingredients

SOLVENT NAPHTHA (PETROLEUM), (CAS N.64742-95-6): applicable note P of enclosed N.1 - Concentration of Benzene < 0,1% in weight. THIS SUBSTANCE IS NOT CLASSIFIED AS CARCINOLOGIC.

Name	Concentr.(C)	Classification
SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM N° Cas 64742-94-5 N° CE 265-198-5 N° Index 649-424-00-3	79,3 <= C < 83,4	Xn R65
2-METHOXY-1-METHYLETHYL ACETATE N° Cas 108-65-6 N° CE 203-603-9 N° Index 607-195-00-7	10,7 <= C < 12,3	R10 Xi R36
MESITYLENE N° Cas 108-67-8 N° CE 203-604-4 N° Index 601-025-00-5	0,49 <= C < 0,6	R10 Xi R37 N R51/53
1,2,4-TRIMETHYLBENZENE N° Cas 95-63-6 N° CE 202-436-9 N° Index 601-043-00-3	8,4 <= C < 9,5	R10 Xn R20 Xi R36/37/38 N R51/53

The complete text of -R- phrases is specified in section 16.SOLVENT NAPHTHA (PETROLEUM), (CAS N.64742-95-6): applicable note P of enclosed N.1 - Concentration of Benzene < 0,1% in weight. THIS SUBSTANCE IS NOT CLASSIFIED AS CARCINOLOGIC.

### 3. Hazards Identification

# DP-MS SLOW THINNER

Revision nr. 1  
Dated 09/06/2007  
Printed on 09/06/2007  
Page n.2 / 6

## 3.1 Substance/Preparation Classification

This preparation is dangerous under 67/548/EEC and 1999/45/EC regulations and subsequent amendments. This material requires a safety data sheet according to the 91/155/EC regulation and subsequent amendments. Further information on health and/or environmental hazards can be found in sections 11 and 12 of this sheet.

Danger Symbols: Xn

Phrases R:  
10-65

## 3.2 Danger Identification

Because of its chemical-physical features, this product is graded as flammable (flash-point 21 °C or higher and 55 °C or lower ).

HARMFUL: MAY CAUSE LUNG DAMAGE IF SWALLOWED.

## 4. First aid measures

EYES: Irrigate copiously with clean, fresh water for at least 15 minutes. Seek medical advice.

SKIN: Wash immediately with plenty of water. Remove contaminated clothing. If irritation persists seek medical attention. Wash contaminated clothing before using them.

INHALATION: Remove to fresh air. If breathing is irregular seek medical advice.

INGESTION: Obtain immediate medical attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person.

## 5. Fire-fighting measures

Closed containers exposed to the heat of a fire may lead to pressure rise and explode. For information on environmental and health risks, protection of the respiratory airways, ventilation and individual protective measures refer to the other sections of this sheet.

Extinguishing measures: CO<sub>2</sub>, foam, AFFF, chemical powder for flammable liquids. Water may not be effective to extinguish the fire, nevertheless it should be used to cool the containers exposed to flames and prevent fires and explosions. For leakage and spillage that have not caught fire, nebulized water may be used to disperse the flammable vapours and protect the people involved in stopping the leakage.

Equipment: wear equipment complete with helmet and face shield and protection of the neck, self breathing apparatus at pressure or demand, insulated jacket and trousers, with bands around the arms, legs and waist.

## 6. Accidental release measures

Extinguish the sources of ignition or heat; cover the spillage with absorbent material. Collect the spilt material and discard the remainder spraying water, if not concentrated (see section 10). For information on environmental and health risks, protection of the respiratory airways, ventilation and individual protective measures, refer to the other sections of this sheet.

Spillage in waters: remove the liquid from the surface with flameproof pumps or manual pumps or suitable absorbent material. Resort to sinking and/or dispersion of the product with suitable substances in open waters, if permitted by the law. The product can be separated from the effluents with oil separators.

## 7. Handling and storage

Store in a well ventilated place keeping the containers closed when not used. Do not smoke while handling. Keep far away from sources of heat, naked flames and sparks and other sources of ignition; do not spray in the vicinity of flames or incandescent materials.

For information on environmental and health risks, protection of the respiratory airways, ventilation and individual protective measures refer to the other sections of this sheet.

# DP-MS SLOW THINNER

Revision nr. 1  
Dated 09/06/2007  
Printed on 09/06/2007  
Page n.3 / 6

## 8. Exposure controls / personal protection.

SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM			
- TLV TWA	650	mg/m3	ACGIH
2-METHOXY-1-METHYLETHYL ACETATE			
- TLV TWA	270	mg/m3	MAK
MESITYLENE			
- TLV TWA	125	mg/m3	NIOSH
1,2,4-TRIMETHYLBENZENE			
- TLV TWA	123	mg/m3	ACGIH
TLV of solvent mixture:	176	mg/mc	

In order to minimize exposure as far as possible, it is strongly recommended to use adequate individual protective measures such as: masks suitable for the product, goggles, gloves and overalls. Do not eat, drink or smoke while handling it. Accurately wash the hands with soap and water before meals and at the end of the work shift.

## 9. Physical and chemical properties

Colour	transparent
Odour	ethereal, slight
State	liquid
Solubility	N.A.
Water solubility	none
Viscosity	N.A.
Vapour density	N.A.
Evaporation speed	N.A.
Comburent properties	N.A.
Partition coefficient: n-octanol/water	N.A.
pH	N.A.
Boiling point	168°C
Melting point	< -20°C
Flash point	> 38°C
Explosive properties	N.A.
Ignition temperature	> 320°C
Vapour pressure	N.A.mmHg
Distillation range	142 - 178
Molecular weight	1
Specific gravity	0,879Kg/l

## 10. Stability and reactivity

The product is stable in normal conditions of use and storage. When heated or in the event of a fire, carbonoxides may be released and vapours which are dangerous to health. The vapours may also form explosive mixtures with the air.

Petroleum naphtha solvent: it can give flammable mixtures with air.

1-methoxy-2-propylacetate: it is stable but in presence of air, it can gradually form peroxides which explode due to the rise in temperature. It can react violently with oxidizing agents and strong acids and alkaline metals. Avoid copper, aluminium and their alloys when storing. Store under inert atmosphere, repaired from humidity because it easily hydrolyses.

## 11. Toxicological information

The introduction of even small quantities of this liquid into the respiratory system during ingestion or vomit may cause bronchopneumonia and pulmonary edema.

1-methoxy-2-propanol and corresponding acetate: the main route of entry is the skin, whereas the respiratory route is less important owing to the low vapour tension of the product. Concentrations above 100 ppm cause irritation of the eyes, nose and oropharynx.

The recommended limit of exposure is 100 ppm for 8 hours. At 1000 ppm disturbance in the equilibrium and severe irritation of the eyes is observed. (For further details refer to INRS, Fiche toxicologique, nr. 221).

Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and ocular irritation on direct contact. No chronic effects have been reported in man. In vitro genotoxicity tests on animals resulted to be negative.

No significant effects were observed in studies on animal reproduction.

The following experimental data confirm that the substance is not even harmful: oral LD50 in the rat = 7900 mg/kg, inhalation CL50 in the rat 4 hours = 55.2 mg/l (Fiche toxicologique nr. 221).

## 12. Ecological information

Petroleum distillates, charcoal, vegetable extracts: they are mixtures of paraffinic, naphthenic, diterpenic and aromatic hydrocarbons. Their behaviour on the environment depends on the concentration. In each case use, according to good working practices, avoiding disposal in the environment. As a rule, the product is poorly bio degradable.

## 13. Disposal considerations

Consider the possibility of burning the product in a suitable incinerator. Acid or basic products must always be neutralized before undergoing any treatment, including biological treatment whenever feasible. If the waste is solid, it can be disposed of in a landfill.

## 14. Transport informations

These goods must be transported by vehicles authorized to the carriage of dangerous goods according to the provisions set out in the current edition of the Code of International Carriage of Dangerous Goods by Road (ADR) and in all the applicable national regulations. These goods must be packed in their original packing or in packing made of materials resistant to their content and not reacting dangerously with it. People loading and unloading dangerous goods must be trained on all the risks deriving from these substances and on all actions that must be taken in case of emergency situations.

Road and rail transport:

ADR:	3	UN:1263
Packing Group:	III	
Label:	3	
Nr. Kemler:	30	
Proper Shipping Name:	Paint or paint related material	
Special Provision:	640E	

Carriage by sea (shipping):

IMO class:	3	UN:1263
Packing Group:	III	

# DP-MS SLOW THINNER

Revision nr. 1  
Dated 09/06/2007  
Printed on 09/06/2007  
Page n.5 / 6

EMS: 3-05  
Marine Pollutant  
Proper Shipping Name: Paint or paint related material

Transport by air:

IATA: 3 UN:1263  
Packing Group: III  
Label: 3  
Cargo:  
Packaging instructions: 310 Maximum quantity: 220 L  
Pass.:  
Packaging instructions: 309 Maximum quantity: 60 L

## 15. Regulatory information



R10 FLAMMABLE.  
R65 HARMFUL: MAY CAUSE LUNG DAMAGE IF SWALLOWED.  
S13 KEEP AWAY FROM FOOD, DRINK AND ANIMAL FEEDINGSTUFFS.  
S62 IF SWALLOWED, DO NOT INDUCE VOMITING: SEEK MEDICAL ADVICE IMMEDIATELY AND SHOW THIS CONTAINER OR LABEL.

Contains:  
SOLVENT NAPHTA (PETROLEUM), HEAVY AROM

Danger labelling under regulations 67/548/CEE and 1999/45/CE and following amendments and adjustments.

Workers exposed to this chemical agent must undergo health checks according to regulation 98/24/CE.

## 16. Other information

Text of -R- phrases quoted in section 2 of the sheet.

R10 FLAMMABLE.  
R20 HARMFUL BY INHALATION.  
R36 IRRITATING TO EYES.  
R36/37/38 IRRITATING TO EYES, RESPIRATORY SYSTEM AND SKIN.  
R37 IRRITATING TO RESPIRATORY SYSTEM.  
R51/53 TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.  
R65 HARMFUL: MAY CAUSE LUNG DAMAGE IF SWALLOWED.

# DP-MS SLOW THINNER

Revision nr. 1  
Dated 09/06/2007  
Printed on 09/06/2007  
Page n.6 / 6

## GENERAL BIBLIOGRAPHY

1. Regulation 1999/45/CE and following amendments;
2. Regulation 67/548/CEE and following amendments and adjustments (technical adjustment XXVIII);
3. Regulation 91/155/CEE and following amendments;
4. The Merck Index. - 10th Edition;
5. Handling Chemical Safety;
6. Niosh - Registry of Toxic Effects of Chemical Substances;
7. INRS - Fiche Toxicologique (toxicological sheet);
8. Patty - Industrial Hygiene and Toxicology;
9. N.I. Sax-Dangerous properties of Industrial Materials-7, 1989 Edition;

## Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product .

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

**THIS PRODUCT IS SUITABLE FOR PROFESSIONAL USE ONLY.**