ΙΝΚϾUPS

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 453/2010 - United Kingdom (UK)

SAFETY DATA SHEET

GL PRIMER

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product no.	:	1423758
Product name	:	GL PRIMER

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Printing inks, coatings, toners, and related materials

Uses advised against: Not Available

1.3 Details of the supplier of the safety data sheet

Inkcups Corporation 310 Andover St. Danvers Massachusetts 01923 United States

1.4 Emergency telephone number

24 Hour Emergency Phone	:	800.535.5053 INFOTRAC 24 Hour Spill and Emergency (+1 352 323 3500 outside of North America)
National advisory body/Poison (<u>Center</u>	
Telephone number	:	Not available.
Hours of operation	:	Not available.
Information limitations	:	Not available.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition

: Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 2, H225 Skin Corr./Irrit. 2, H315 Eye Dam./Irrit. 2, H319 The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

2.2 Label elements

Hazard pictograms	
Signal word Hazard statements	 Danger Highly flammable liquid and vapor. Causes serious eye irritation. Causes skin irritation.
Precautionary statements	
General Prevention	 Read label before use. Wear protective gloves. Wear eye or face protection. Keep away from heat, sparks, open flames and hot surfaces No smoking. Use explosion-proof electrical, ventilating, lighting and all material-
Response	 handling equipment. IF ON SKIN (or hair): Take off immediately all contaminated
Storage Disposal	 clothing. Rinse skin with water or shower. Keep cool. Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	: 2-Propenoic acid, 3-(trimethoxysilyl)propyl ester
Supplemental label elements	: Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Special packaging requirements	
Containers to be fitted with child-resistant fastenings	: Not applicable.
Tactile warning of danger	: Yes, applicable.
2.3 Other hazards	
Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII	: Not applicable.
Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	: Not applicable.
Other hazards which do not result in classification	: None known.
Version: 2.6 Date of issu	e/Date of revision: 18.03.2016 Date of previous issue: 18.03.2016

SECTION 3: Composition/information on ingredients

3.1 Substances

: Not applicable

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	<u>Classification</u> Regulation (EC) No. 1272/2008 [CLP]	Туре
ethanol	EC:200-578-6 CAS : 64-17-5 Index:603-002- 00-5	>=70 - <90	Flam. Liq. 2, H225	[2]
propyl acetate	EC:203-686-1 CAS : 109-60-4 Index:607-024- 00-6	>=3 - <5	Flam. Liq. 2, H225 Eye Dam./Irrit. 2, H319 STOT SE 3, H336	[1][2]
propan-2-ol	EC:200-661-7 CAS : 67-63-0 Index:603-117- 00-0	>=3 - <5	Flam. Liq. 2, H225 Eye Dam./Irrit. 2, H319 STOT SE 3, H336	[1][2]
2-Propenoic acid, 3- (trimethoxysilyl)propyl ester	EC: Index:	>=2 - <3	Acute Tox. 4, H332 (inhalation) Skin Corr./Irrit. 1B, H314 Eye Dam./Irrit. 1, H318 Aquatic Chronic 3, H412	[1]

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

See Section 16 for the full text of the R phrases or H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	upper and	l lower eyelids. Chec	lenty of water, occasions for and remove any 0 minutes. Get medica	contact lenses.
Inhalation	for breath	ning. If not breathing	d keep at rest in a posi , if breathing is irregul ide artificial respiratio	lar or if
Version: 2.6	Date of issue/Date of revision:	18.03.2016	Date of previous issue:	18.03.2016

		trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	:	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Eye contact Inhalation Skin contact Ingestion <u>Over-exposure signs/symptoms</u>	:	Causes serious eye irritation. No known significant effects or critical hazards. Causes skin irritation. Irritating to mouth, throat and stomach.
Eye contact	:	Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	:	No specific data.
Skin contact	:	Adverse symptoms may include the following: irritation redness
Ingestion	:	No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician			ct poison treatment sp s have been ingested o	
Specific treatments		ic treatment.	s have been nigested (n minaleu.
Version: 2.6	Date of issue/Date of revision:	18.03.2016	Date of previous issue:	18.03.2016

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media	:	Use dry chemical, CO#, water spray (fog) or foam. Do not use water jet.
5.2 Special hazards arising from the	subs	tance or mixture
Hazards from the substance or mixture	:	Highly flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.
Hazardous thermal decomposition products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide
5.3 Advice for firefighters		
Special protective actions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self- contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.
Additional information	:	Not available.
SECTION 6: Acciden	tal	release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Version:2.6Date of issue/Date of revision:	18.03.2016	Date of previous issue:	18.03.2016
--	------------	-------------------------	------------

6.3 Methods and materials for containment and cleaning up

Small spill Large spill	:	Stop leak if without risk. Move containers from spill area. Use spark- proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. Stop leak if without risk. Move containers from spill area. Use spark- proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non- combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures Advice on general occupational hygiene	not inge breathin appropri- storage in the or compati- use awa Use exp handling precauti- containe : Eating, this mat hands an contami		ting, drinking and smoking should be prohibited in areas is material is handled, stored and processed. Workers sho nds and face before eating, drinking and smoking. Remo ntaminated clothing and protective equipment before ent ting areas. See also Section 8 for additional information		ng. Avoid tillation. Wear e. Do not enter ventilated. Keep made from a use. Store and ignition source. and material Take ges. Empty ous. Do not reuse n areas where ters should wash . Remove ore entering	
7.2 Conditions for safe storage, including any incompatibilities	:	approved sunlight in incompati	area. Store in n a dry, cool a ble materials	th local regulations. original container p and well-ventilated a (see Section 10) and ources. Separate from	orotected area, awa 1 food ar	from direct by from ad drink.
Version: 2.6 Date of issue/	Date	of revision:	18.03.2016	Date of previou	ıs issue:	18.03.2016

Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Seveso II Directive - Reporting thresholds

Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
P5c: Flammable liquids 2 and 3 not falling under P5a or P5b	5.000 kg	50.000 kg
C7b: Highly flammable (R11)	5.000 kg	50.000 kg

7.3 Specific end use(s)

Recommendations	:	Not available.
Industrial sector specific	:	Not available.
solutions		

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker or exposure or environmental releases.

8.1 Control parameters

Product/ingredient name	Exposure limit values
ethanol	
propyl acetate	EH40/2005 WELs (1997-01-01) Short Term Exposure Limit 1.060 mg/m3 , 250 ppm EH40/2005 WELs (1997-01-01) Time Weighted Average (TWA) 849 mg/m3 , 200 ppm
propan-2-ol	EH40/2005 WELs (1997-01-01) Short Term Exposure Limit 1.250 mg/m3, 500 ppm EH40/2005 WELs (1997-01-01) Time Weighted Average (TWA) 999 mg/m3, 400 ppm

Occupational exposure limits

Recommended monitoring procedures	: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous
Version: 2.6 Date of issue/	ate of revision: 18.03.2016 Date of previous issue: 18.03.2016

Page:8/17

		substances will also be required.
DNEL/DMEL Summary	:	Not available.
PNEC Summary	:	Not available.
8.2 Exposure controls		
Appropriate engineering controls	:	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Individual protection measures		
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product., When there is a risk of ignition from static electricity, wear anti-static protective clothing., For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves., Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this
Respiratory protection	:	product. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or
Version: 2.6 Date of issue	Date	of revision: 18.03.2016 Date of previous issue: 18.03.2016

Environmental exposure controls	:	anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
		y 1

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	:	liquid
Color	:	Pink
Odor	:	Not available.
Odor threshold	:	Not available.
рН	:	Not available.
Melting point/freezing point	:	Not available.
Initial boiling point and boiling	:	Not available.
range		
Flash point	:	12,8 °C
		< 23 °C Not Measured. Flashpoint is estimated to be < 23 °C (73 °F).
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Upper/lower flammability or	:	Lower: Not available.
explosive limits		Upper: Not available.
Vapor pressure	:	Not available.
Vapor density	:	Not available.
Relative density	:	0,82
·		
Solubility(ies)	:	Not available.
Partition coefficient: n-	:	Not available.
octanol/water		
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
Viscosity	:	Dynamic: Not available.
		Kinematic: Not available.
Explosive properties	:	Not available.
Oxidizing properties	:	Not available.
9.2 Other information		
Volatile.	:	98 %(m) Weight %
		99,81 %(V) Volume %
VOC %	:	89,98 %(m) Weight %
		93,22 %(V) Volume %
Coating VOC	:	6,6 lb/gal
		791 g/l

9

SECTION 10: Stability and reactivity

10.1 Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	:	The product is stable.
10.3 Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	:	Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
10.5 Incompatible materials	:	Reactive or incompatible with the following materials: oxidizing materials
10.6 Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Ethanol				
	LD50 Oral	Rat	15.010 mg/kg	-
	LD50 Oral	Rat	7.000 mg/kg	-
	LC50	Rat	20000 ppm	10 h
	Inhalation			
	LC50	Rat	6 mg/l	6 h
	Inhalation			
	LC50	Rat	125 mg/l	4 h
	Inhalation			
Acetic acid, propyl ester				
	LD50 Oral	Rat	9.370 mg/kg	-
Isopropanol				
	LD50 Oral	Rat	5.000 mg/kg	-
	LD50 Oral	Rat	5.045 mg/kg	-
	LC50	Rat	16000 ppm	8 h
	Inhalation			
	LD50 Dermal	Rabbit	12.800 mg/kg	-

Silane component **Conclusion/Summary**

: Not available.

Acute toxicity estimates

Not available.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
propyl acetate	Eyes - Mild	Rabbit	-	24 hrs	-
	irritant				
propyl acetate	Skin - Mild	Rabbit	-		-
	irritant				
propan-2-ol	Eyes -	Rabbit	-	24 hrs	-
	Moderate				
	irritant				
propan-2-ol	Skin - Mild	Rabbit	-		-
	irritant				
propan-2-ol	Eyes -	Rabbit	-		-
	Severe				
	irritant				
propan-2-ol	Eyes -	Rabbit	-		-
	Moderate				
	irritant				
Conclusion/Summary					
Skin		ot available.			
Eyes		ot available.			
Respiratory	: No	ot available.			
<u>Sensitization</u>					
Conclusion/Summary					
Skin	: No	ot available.			
Respiratory	: No	ot available.			
<u>Mutagenicity</u>					
Conclusion/Summary	: No	ot available.			
Carcinogenicity					
Conclusion/Summary	: No	ot available.			
<u>Reproductive toxicity</u>					
Conclusion/Summary	: No	ot available.			
<u>Teratogenicity</u>					
Conclusion/Summary	: No	ot available.			

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
propyl acetate	Category 3		Narcotic effects
propan-2-ol	Category 3		Narcotic effects

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Page: 12/17

Information on the likely routes of exposure	:	Not available.
Potential acute health effects		
Eye contact Inhalation Skin contact Ingestion	: : :	Causes serious eye irritation. No known significant effects or critical hazards. Causes skin irritation. Irritating to mouth, throat and stomach.
Symptoms related to the physical, c	hemic	cal and toxicological characteristics
Eye contact	:	Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	:	No specific data.
Skin contact	:	Adverse symptoms may include the following: irritation redness
Ingestion	:	No specific data.
Delaved and immediate effects and a	lso ch	pronic effects from short and long term exposure
Short term exposure		
Potential immediate effects Potential delayed effects	:	Not available. Not available.
Long term exposure		
Potential immediate effects Potential delayed effects	:	
Potential chronic health effects		
Conclusion/Summary	:	Not available.
General Carcinogenicity Mutagenicity Teratogenicity Developmental effects Fertility effects	:	No known significant effects or critical hazards. No known significant effects or critical hazards.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	e Result	Species	Exposure
ethanol			
	Acute LC50 13.480.000 µg/l Fresh water	Fish - Fathead minnow	96 h
Version: 26	Date of issue/Date of revision: 180	3 2016 Date of previo	us issue: 18.03.2016

Version: 2.6

	Acute LC50 42.000 µg/l	Fish - Rainbow	96 h
	Fresh water	trout,donaldson trout	
	Acute LC50 100 mg/l	Fish - Fathead minnow	96 h
	Fresh water		
	Acute LC50 12.720	Fish - Fathead minnow	96 h
	mg/l Fresh water		
	Acute LC50 5.680 mg/l	Aquatic invertebrates.	48 h
	Fresh water	Water flea	
	Acute EC50 2.000 µg/l	Aquatic invertebrates.	48 h
	Fresh water	Water flea	
	Acute LC50 9.248.000	Aquatic invertebrates.	48 h
	µg/l Fresh water	Water flea	
	Acute LC50 9.268.000	Aquatic invertebrates.	48 h
	µg/l Fresh water	Water flea	
	Acute EC50 100 mg/l	Aquatic invertebrates.	48 h
	Fresh water	Water flea	
	Acute EC50 20.000	Aquatic plants - Green	96 h
	mg/l Fresh water	Flagellate	
	Acute EC50 17,921	Aquatic plants - Green	96 h
	mg/l Marine water	algae	
	Acute EC50 10.000	Aquatic plants - Algae	96 h
	mg/l Fresh water		
propan-2-ol			
	Acute LC50 1.400.000	Fish - Western	96 h
	μg/l	mosquitofish	
	Acute LC50 4.200 mg/l	Fish - Harlequinfish, red	96 h
	Fresh water	rasbora	
	Acute LC50 9.640.000	Fish - Fathead minnow	96 h
	µg/l Fresh water		
	Acute LC50 6.550.000	Fish - Fathead minnow	96 h
	µg/l Fresh water		
	Acute LC50 1.400.000	Fish - Bluegill	96 h
	μg/l		
Conclusion/Summary	Not available		

Conclusion/Summary

: Not available.

12.2 Persistence and degradability

Conclusion/Summary	:	Not available.
12.3 Bioaccumulative potential12.4 Mobility in soil		
Soil/water partition coefficient (KOC)	:	Not available.
Mobility	:	Not available.
12.5 Results of PBT and vPvB asse	ssment	
РВТ	:	P: Not available. B: Not available. T: Not available.
vPvB	:	vP: Not available.

Version: 2.6 Date of issue/Date of revision: 18.03.2016 Date of previous issue: 18.03.2016

Page: 14/17

vB: Not available.

12.6 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product Methods of disposal The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. The classification of the product may meet the criteria for a Hazardous waste hazardous waste. Packaging Methods of disposal The generation of waste should be avoided or minimized wherever : possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. **Special precautions** This material and its container must be disposed of in a safe way. : Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

Regulatory information	Proper shipping name	UN - Number	Hazard classification	Packing group	Additional information
ADN	Printing ink related material	UN1210	3	II	
ADR	Printing ink related material	UN1210	3	II	
ΙΑΤΑ	Printing ink related material	UN1210	3	II	
IMDG	Printing ink related material	UN1210	3	II	

Version: 2.6 Date of issue/Date of revision: 18.03.2016 Date of previous issue: 18.03.2016

DOT (U.S.A.)	Printing ink	UN1210	3	Π	
(Pictograms)	related material				
Mexico Classification	Printing ink	UN1210	3	Π	
	related material				
TDG Class	Printing ink	UN1210	3	Π	
	related material				

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH) Annex XIV - List of substances subject to authorization Annex XIV: None of the components are listed.

Substances of very high concern: **Other EU regulations**

Europe inventory Integrated pollution prevention and control list (IPPC) - Air	:	Not determined.Not determined. Not listed
Integrated pollution prevention and control list (IPPC) - Water	:	Not listed
Aerosol dispensers	:	Not applicable.

Seveso II Directive

This product is controlled under the Seveso II Directive.

Category P5c: Flammable liquids 2 and 3 C7b: Highly flammable (R11)	not f	alling under P5a or P5b
National regulations References	:	 Guide de la loi et du règlement sur le transport des marchandises dangeureuses au Canada. Centre de conformité international Ltée. 1986.
International regulations		
Chemical Weapons Convention List Schedule I Chemicals	:	Not listed
Chemical Weapons Convention	:	Not listed
List Schedule II Chemicals Chemical Weapons Convention List Schedule III Chemicals	:	Not listed
15.2 Chemical Safety Assessment	:	This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Abbreviations and acronyms	:	ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DNEL = Derived No Effect Level DMEL = Derived Minimal Effect Level EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number vPvB = Very Persistent and Very Bioaccumulative
Key literature references and sources for data	:	- Guide de la loi et du règlement sur le transport des marchandises dangeureuses au Canada. Centre de conformité international Ltée. 1986.

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Flam. Liq. 2, H225	On basis of test data
Skin Corr./Irrit. 2, H315	Calculation method
Eye Dam./Irrit. 2, H319	Calculation method

Full text of abbreviated H	: H332 (inhalation)	Harmful if inhaled.
statements	H412	Harmful to aquatic life with long
		lasting effects.
	H318	Causes serious eye damage.
	H319	Causes serious eye irritation.
	H225	Highly flammable liquid and
		vapor.
	H314	Causes severe skin burns and
		eye damage.
	H315	Causes skin irritation.
	H336	May cause drowsiness and
		dizziness.
Full text of classifications	: Acute Tox. 4, H332	ACUTE TOXICITY (inhalation)
[CLP/GHS]	· Acute 10x. 7, 11352	- Category 4
	Aquatic Chronic 3, H412	AQUATIC HAZARD (LONG-
	•	TERM) - Category 3
	Eye Dam./Irrit. 1, H318	SERIOUS EYE DAMAGE/
		EYE IRRITATION - Category 1
	Eye Dam./Irrit. 2, H319	SERIOUS EYE DAMAGE/
		EYE IRRITATION - Category 2
	Flam. Liq. 2, H225	FLAMMABLE LIQUIDS -
		Category 2
	Skin Corr./Irrit. 1B, H314	SKIN
		CORROSION/IRRITATION -
		Category 1B
	Skin Corr./Irrit. 2, H315	SKIN
		CORROSION/IRRITATION -
		Category 2

		STOT SE 3, H336	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 3
Date of printing	:	05.01.2018	
Date of issue/ Date of revision	:	18.03.2016	
Date of previous issue	:	18.03.2016	
Version	:	2.6	

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.