

SAFETY DATA SHEET

Fast Cure High Opacity White

SECTION 1: IDENTIFICATION

- 1.1. Product identifier

Trade name:

Fast Cure High Opacity White

Product no.:

NS-R White
- 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Industrial purposes, Printing inks

Restricted to professional users.

Uses advised against :

None known.
- 1.3. Details of the supplier of the safety data sheet

Company and address:

INKCUPS CORP.

310 ANDOVER ST.

DANVERS, MA 01923

USA

978-646-8980

E-mail:

compliance@inkcups.com

SDS date:

7/29/2025

SDS Version:

1.0
- 1.4. Emergency telephone number

CHEMTREC 800-424-9300 24hr

SECTION 2: HAZARD(S) IDENTIFICATION

- OSHA/HCS status

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)
- 2.1. Classification of the substance or mixture

Acute

Tox. 4; H302, Harmful if swallowed.

Skin Corr. 1C; H314, Causes severe skin burns and eye damage.

Skin Sens. 1; H317, May cause an allergic skin reaction.

Eye Dam. 1; H318, Causes serious eye damage.

Repr. 1B; H360, May damage fertility or the unborn child.

2.2. Label elements

Hazard pictogram(s):



Signal word:

Danger

<i>Hazard statement(s):</i>	Harmful if swallowed. (H302) Causes severe skin burns and eye damage. (H314) May cause an allergic skin reaction. (H317) May damage fertility or the unborn child. (H360)
<i>Precautionary statement(s):</i>	
<i>General:</i>	-
<i>Prevention:</i>	Obtain special instructions before use. (P201) Do not handle until all safety precautions have been read and understood. (P202) Do not breathe vapor/mist/dust/fume/gas/spray. (P260) Wash hands and exposed skin thoroughly after handling. (P264) Contaminated work clothing should not be allowed out of the workplace. (P272) Wear face protection/protective gloves/protective clothing. (P280) Keep container tightly closed. (P233) Avoid release to the environment. (P273)
<i>Response:</i>	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. (P301+P330+P331) IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. (P303+P361+P353) IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338) IF exposed or concerned: Get medical advice/attention. (P308+P313) Immediately call a POISON CENTER/doctor. (P310) If skin irritation or rash occurs: Get medical advice/attention. (P333+P313) Take off contaminated clothing and wash it before reuse. (P362+P364)
<i>Storage:</i>	Store in a well-ventilated place. (P403)
<i>Disposal:</i>	Dispose of contents/container in accordance with local regulation. / in accordance with regional regulation. / in accordance with national regulation. / in accordance with international regulation. (P501)
<i>Additional labelling:</i>	Not applicable.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Tetrahydrofurfuryl acrylate	CAS No.: 2399-48-6	15-25%	1, HHNOC071 Acute Tox. 4, H302 Skin Corr. 1C, H314 Skin Sens. 1B, H317 Eye Dam. 1, H318 Repr. 1B, H360	
Pentaerythritol, ethoxylated, esters with acrylic acid	CAS No.: 51728-26-8	10-15%	Skin Irrit. 2, H315 Eye Irrit. 2, H319	
Ethyl phenyl(2,4,6trimethylbenzoyl)phosphinate	CAS No.: 84434-11-7	10-15%	Skin Sens. 1B, H317	
Oxybis(methyl-2,1ethanediyl) diacrylate	CAS No.: 57472-68-1	10-15%	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Dam. 1, H318	
hexane-1,6-diol diacrylate	CAS No.: 13048-33-4	5-10%	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319	
2-Propenoic acid, 2- [2(ethenyloxy)ethoxy]ethyl ester	CAS No.: 86273-46-3	5-10%	Acute Tox. 4, H302 Skin Sens. 1, H317	
phenyl bis(2,4,6trimethylbenzoyl)phosphine oxide	CAS No.: 162881-26-7	3-5%	Skin Sens. 1A, H317	
2-phenoxyethyl acrylate	CAS No.: 48145-04-6	<1%	Skin Sens. 1A, H317 Repr. 2, H361	
Propylidynetrimethanol	CAS No.: 77-99-6	<1%	Repr. 2, H361fd	
tetrahydro-2-furylmethanol; tetrahydro furfuryl alcohol	CAS No.: 97-99-4	<0.25%	Eye Irrit. 2, H319 Repr. 1B, H360Df	
Tris(N-hydroxy- NnitrosophenylaminatoO,O')aluminium	CAS No.: 15305-07-4	<0.25%	Acute Tox. 4, H302 Skin Sens. 1B, H317	

Where the concentration of an ingredient is expressed as a range the exact concentration has been withheld as a trade secret.

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

-

SECTION 4: FIRST-AID MEASURES

4.1. Description of first aid measures

General information:	If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 911 and give immediate treatment (first aid). Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.
Inhalation:	Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.
Skin contact:	Flush exposed area with water for a long time - at least 30 minutes. It may be necessary to flush for several hours. Use a comfortable water temperature (20-30 °C). Contact Poison Information/doctor/hospital for further advice on follow-up and treatment. Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.
Eye contact:	If skin irritation occurs: Get medical advice/attention. If in eyes: Flush eyes with plenty of water or salt water (20-30 °C) for at least 30 minutes and continue until irritation stops. Remove contact lenses. Make sure you flush under the upper and lower eyelids. Seek medical assistance immediately and continue flushing during transport.
Ingestion:	In the case of ingestion, contact a doctor immediately. If the person is conscious, give them water. DO NOT try to induce vomiting unless this is recommended by a doctor. Hold head facing down to prevent vomit from returning to the mouth and throat. Prevent shock by keeping the injured person warm and calm. Initiate immediate resuscitation if breathing stops. If unconscious, roll the injured person into recovery position. Call an ambulance.
Burns:	Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Sensitization: This product contains substances, which may trigger allergic reaction upon dermal contact. Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

Tissue-damaging effects: This product contains substances with skin corrosive properties. Inhaled vapor or aerosols may produce adverse effects to lungs, irritations and burns in the respiratory organs as well as coughing. Dermal contact and contact with the eye cause irreversible effects.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire extinguishing water to enter the sewage system and nearby surface waters. If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are: Carbon oxides (CO / CO₂)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact the Poison Help Line on 1-800-222-1222 (24/7) in order to obtain further advice.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances.

Ensure adequate ventilation, especially in confined areas.

Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

Keep unauthorized persons away from the spill

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid direct contact with the product.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material: Keep only in original packaging.

Storage conditions: 5 - 30°C

Protect from sunlight.

Incompatible materials: No specific requirements

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

titanium dioxide

Long term exposure limit (ACGIH TLV) (mg/m³): 10

Long term exposure limit (NIOSH REL) (mg/m³): Potential occupational carcinogen; (ultrafine particles) / 2.4 (fine) / 0.3 (ultrafine)

toluene

Short term exposure limit (STEL) (NIOSH REL) (ppm): 150

Long term exposure limit (ACGIH TLV) (ppm): 20

ethylbenzene

Short term exposure limit (STEL) (NIOSH REL) (ppm): 125

Long term exposure limit (OSHA Table Z-1) (mg/m³): 435

Long term exposure limit (OSHA Table Z-1) (ppm): 100

Long term exposure limit (ACGIH TLV) (ppm): 20

Part 1910 - Occupational Safety and Health Standards (29 CFR 1910.1000 TABLE Z-1 - Limits for Air Contaminants)

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

<i>General recommendations:</i>	Smoking, drinking and consumption of food is not allowed in the work area.
<i>Exposure scenarios:</i>	There are no exposure scenarios implemented for this product.
<i>Exposure limits:</i>	Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.
<i>Appropriate technical measures:</i>	The formation of vapors must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked. Ensure that eyewash stations and safety showers are located within easy reach. Apply standard precautions during use of the product. Avoid inhalation of vapors.
<i>Hygiene measures:</i>	In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.
<i>Measures to avoid environmental exposure:</i>	Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

Generally: Use only protective equipment with a recognized certification mark, e.g. the UL mark.

Respiratory Equipment:

Respiratory protection is not needed in the event of adequate ventilation.

In case of insufficient ventilation, wear suitable respiratory equipment. Approved organic vapor respirator



Skin protection:

Dedicated work clothing should be worn.



Hand protection:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Eye protection:

In the likelihood of direct or incidental exposure, use face protection. (EN166)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

<i>Physical state:</i>	Liquid
<i>Color:</i>	White
<i>Odor:</i>	Faint
<i>Odor threshold (ppm):</i>	No data available.
<i>pH:</i>	Not applicable
<i>Density (g/cm³):</i>	1.2 (25 °C)
<i>Kinematic viscosity:</i>	No data available
<i>Particle characteristics:</i>	Does not apply to liquids.

Phase changes

<i>Melting point/freezing point (°F):</i>	No data available.
<i>Softening point/range (°F):</i>	Does not apply to liquids.
<i>Boiling point (°F):</i>	No data available
<i>Vapor pressure:</i>	No data available.
<i>Relative vapor density:</i>	No data available.
<i>Decomposition temperature</i>	No data available.

(°F): Data on fire and explosion hazards

<i>Flash point (°F):</i>	Not applicable
<i>Flammability (°F):</i>	No data available.
<i>Auto-ignition temperature (°F):</i>	No data available.
<i>Explosion limits (% v/v):</i>	No data available.

Solubility

<i>Solubility in water:</i>	No data available
<i>n-octanol/water coefficient (LogKow):</i>	No data available.
<i>Solubility in fat (g/L):</i>	No data available.

9.2. Other information

<i>Sensitivity to shock:</i>	No
<i>Other physical and chemical parameters:</i>	No data available.
<i>Oxidizing properties:</i>	No data available.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions, including those associated with foreseeable emergencies

None known.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

No specific requirements

10.6. Hazardous decomposition products

Thermal decomposition may produce corrosive vapors.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects Acute toxicity

Product/substance	hexane-1,6-diol diacrylate
Species:	Rat
Route of exposure:	Oral
Test:	LD50 Result: >5000 mg/kg

Product/substance	hexane-1,6-diol diacrylate
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	3650 mg/kg

Harmful if swallowed.

Skin corrosion/irritation

Product/substance	hexane-1,6-diol diacrylate
Result:	Adverse effect observed (Irritating)

Causes severe skin burns and eye damage.

Serious eye damage/irritation

Product/substance	hexane-1,6-diol diacrylate
Result:	Adverse effect observed (Highly irritating)

Causes serious eye damage.

Respiratory sensitization

Based on available data, the classification criteria are not met.

Skin sensitization

Product/substance	hexane-1,6-diol diacrylate Result:
	Adverse effect observed (sensitizing)

May cause an allergic skin reaction.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

May damage fertility or the unborn child.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Long term effects

Tissue-damaging effects: This product contains substances with skin corrosive properties. Inhaled vapor or aerosols may produce adverse effects to lungs, irritations and burns in the respiratory organs as well as coughing. Dermal contact and contact with the eye cause irreversible effects.

Other information

titanium dioxide has been classified by IARC as a group 2B carcinogen.
toluene has been classified by IARC as a group 3 carcinogen.
ethylbenzene has been classified by IARC as a group 2B carcinogen.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Product/substance hexane-1,6-diol diacrylate
Species: Fish, Oryzias latipes

Duration: 96 hours

Test: LC50

Result: 0.38 mg/L

Product/substance hexane-1,6-diol diacrylate
Species: Crustacean, Daphnia magna

Duration: 48 hours

Test: EC50

Result: 2.7 mg/L ata, the classification criteria are
Based on available d not met.

12.2. Persistence and degradability

Product/substance hexane-1,6-diol diacrylate
Conclusion: Readily biodegradable

12.3. Bioaccumulative potential

Product/substance hexane-1,6-diol diacrylate
LogKow: 2.81 @ 25C
Conclusion: -

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Other adverse effects

None known.

SECTION 13: DISPOSAL CONSIDERATIONS

RCRA Hazardous waste ("P" and "U" list) (40 CFR 261)

toluene is listed with EPA Hazardous Waste Number: U220

Specific labelling Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: TRANSPORT INFORMATION

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
DOT	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (hexane-1,6-diol diacrylate)	Transport hazard class: 9 Label: 9 Classification code: M6 	III	No	Limited quantities: 5 L Tunnel restriction code: (-) See below for additional information.
IMDG	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (hexane-1,6-diol diacrylate)	Transport hazard class: 9 Label: 9 Classification code: M6 	III	No	Limited quantities: 5 L EmS: F-A S-F See below for additional information.
IATA	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (hexane-1,6-diol diacrylate)	Transport hazard class: 9 Label: 9 Classification code: M6 	III	No	See below for additional information.

* Packing group

** Environmental hazards

Additional information

This product is within scope of the regulations of transport of dangerous goods.
Although this product is environmentally hazardous, the environmentally hazardous substance mark has been omitted as the product is supplied in packaging with a maximum quantity of 5 L / 5 kg.
-
DOT / See § 172.101 Hazardous Materials Table for any information on special provisions, requirements, or warnings in connection with transport. See § 172.602, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport. IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.
IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

- 14.6. Special precautions for user Not applicable.
- 14.7. Transport in bulk according to IMO instruments No data available.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. U.S. Federal regulations

<i>TSCA (the non-confidential portion):</i>	Tetrahydrofurfuryl acrylate is listed Pentaerythritol, ethoxylated, esters with acrylic acid is listed Oxybis(methyl-2,1-ethanediyl) diacrylate is listed titanium dioxide is listed hexane-1,6-diol diacrylate is listed 2-Propenoic acid, 2-[2-(ethenyloxy)ethoxy]ethyl ester is listed phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide is listed 2-phenoxyethyl acrylate is listed Propylidynetrimethanol is listed tetrahydro-2-furylmethanol;tetrahydrofurfuryl alcohol is listed Tris(N-hydroxy-N-nitrosophenylaminato-O,O')aluminium is listed toluene is listed ethylbenzene is listed
<i>Clean Air Act:</i>	toluene is regulated as a hazardous air pollutant (HAPS) ethylbenzene is regulated as a hazardous air pollutant (HAPS)
<i>EPCRA Section 302:</i>	None of the components are listed
<i>EPCRA Section 304:</i>	None of the components are listed
<i>EPCRA section 313:</i>	toluene is listed ethylbenzene is listed

CERCLA:

toluene is regulated with a Reportable Quantity (RQ) of:
1000 pounds
ethylbenzene is regulated with a Reportable Quantity (RQ)
of: 1000 pounds
This product is subject to Tier II reporting.

*Hazardous chemical inventory
reporting:*

State regulations

California / Prop. 65:

titanium dioxide is known to cause: cancer
—
toluene is known to cause: Developmental Toxicity
NSRL/MADL (µg/day): 7000 (Level represents absorbed
dose (rounded from 6,525 µg/day)
—
ethylbenzene is known to cause: Cancer
NSRL/MADL (µg/day): 54 (inhalation) 41 (oral)

Massachusetts / Right To Know Act:

—
titanium dioxide is listed
tetrahydro-2-furylmethanol;tetrahydrofurfuryl alcohol is
listed
toluene is listed
ethylbenzene is listed

New Jersey / Right To Know Act:

titanium dioxide / Substance number: 1861
—
toluene / Substance number: 1866
toluene is on the Special Health Hazard Substance List
—
ethylbenzene / Substance number: 0851
ethylbenzene is on the Special Health Hazard Substance
List

New York / Right To Know Act:

—
titanium dioxide is listed
titanium dioxide is regulated with a Threshold Reporting
Quantity (TRQ) of: 100 pounds
—
toluene is listed toluene is regulated with a Reportable
Quantity (RQ) of:
1000 pounds
toluene is regulated with a Threshold Reporting Quantity
(TRQ) of: 0 pounds
—
ethylbenzene is listed
ethylbenzene is regulated with a Reportable Quantity (RQ)
of: 1000 pounds
ethylbenzene is regulated with a Threshold Reporting
Quantity (TRQ) of: 0 pounds
—

Pennsylvania / Right To Know Act:

titanium dioxide is listed

—
tetrahydro-2-furylmethanol; tetrahydrofurfuryl alcohol
is listed —

toluene is listed

toluene is hazardous to the environment (E)

—
ethylbenzene is listed

ethylbenzene is hazardous to the environment (E)

—

15.4. Restrictions for application

Restricted to professional users.

15.5. Demands for specific education

No specific requirements.

15.6. Additional information

Not applicable.

15.7. Chemical safety assessment

No

15.8. Sources

OSHA Hazard Communication Standard (29 CFR 1910.1200)

SECTION 16: OTHER INFORMATION

Full text of H-phrases as mentioned in section 3

Corrosive to the respiratory tract, Corrosive to the respiratory tract.

H302, Harmful if swallowed.

H314, Causes severe skin burns and eye damage.

H315, Causes skin irritation.

H317, May cause an allergic skin reaction.

H318, Causes serious eye damage.

H319, Causes serious eye irritation.

H360, May damage fertility or the unborn child.

H360Df, May damage the unborn child. Suspected of damaging fertility.

H361, Suspected of damaging fertility or the unborn child.

H361fd, Suspected of damaging fertility. Suspected of damaging fertility or the unborn child.

The full text of identified uses as mentioned in section 1

None known.

Abbreviations and acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

ADN = European Provisions concerning the International Carriage of Dangerous Goods by
Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by
Road

ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CERCLA = Comprehensive Environmental Response Compensation and Liability Act
DOT = Department of Transportation
EINECS = European Inventory of Existing Commercial chemical Substances
EPCRA = Emergency Planning and Community Right-To-Know Act
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
HCIS = Hazardous Chemical Information System
HNOC = Hazards Not Otherwise Classified
IARC = International Agency for Research on Cancer
IATA = International Air Transport Association
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
NFPA = National Fire Protection Association
NIOSH = National Institute for Occupational Safety and Health
OECD = Organization for Economic Co-operation and Development
OSHA = Occupational Safety and Health Administration
PBT = Persistent, Bioaccumulative and Toxic
RCRA = Resource Conservation and Recovery Act
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SARA = Superfund Amendments and Reauthorization Act
SCL = A specific concentration limit.
STEL = Short-term exposure limits
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TSCA = The Toxic Substances Control Act
TWA = Time weighted average
UN = United Nations
UVBC = Unknown or variable composition, complex reaction products or of biological materials
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by HCS (29 CFR 1910.1200).

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product.

Information in this safety data sheet cannot be used as a product specification.

Country-language: US-en