Page 1/9

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Date of issue: 08/08/2025 Version: 2.0 Reviewed on 08/04/2025

1 Identification

Product identifier

Product name: Shipping Fluid Other means of identification Article number: ix-shipfluid

Application of the substance / the mixture: Printing inks

Details of the supplier of the safety data sheet

Inkcups Now, LLC 310 Andover Street Danvers, MA 01923 - USA 1-978-646-8980

Manufacturer/Supplier:

Inkcups Now, LLC 310 Andover Street Danvers, MA 01923

USA

Information department: compliance@inkcups.com

Emergency telephone number: Verisk 3E US & Canada: +1 866 519 4752; Access Code: 335740

* 2 Hazard(s) identification

Classification of the substance or mixture

Skin irritation 2 H315 Causes skin irritation.

Eye irritation 2A H319 Causes serious eye irritation.

Sensitization - skin 1 H317 May cause an allergic skin reaction.

Label elements

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). **Hazard pictograms**



GHS07

Signal word Warning

Hazard-determining components of labeling:

hexamethylene diacrylate

Neopentylglycol(PO)2 Diacrylate

Hazard statements

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves / eye protection / face protection.

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Date of issue: 08/08/2025 Version: 2.0 Reviewed on 08/04/2025

Product name: Shipping Fluid

If on skin: Wash with plenty of water.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

Specific treatment (see on this label).

If eye irritation persists: Get medical advice/attention.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

49.5 % of the mixture consists of component(s) of unknown toxicity.

Classification according to (d)(1)(ii) of § 1910.1200

The SDS issuer does not object to the classifications provided by importers or manufacturers of precursor products.

Hazards not otherwise classified

There are no adverse physical or health effects known that are not covered by the hazard classes of the Hazard Communications Standard.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:

13048-33-4 hexamethylene diacrylate

25 - 50%

Skin irritation 2, H315; Eye irritation 2A, H319; Sensitization - skin 1, H317

84170-74-1 Neopentylglycol(PO)2 Diacrylate

25 - 50%

Sensitization - skin 1, H317

4 First-aid measures

Description of first aid measures

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: If symptoms persist consult doctor.

Most important symptoms and effects, both acute and delayed No further relevant information available.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

Extinguishing media

Suitable extinguishing agents: Use fire fighting measures that suit the environment.

Special hazards arising from the substance or mixture No further relevant information available.

Advice for firefighters

Protective equipment: No special measures required.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures Not required.

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Date of issue: 08/08/2025 Version: 2.0 Reviewed on 08/04/2025

Product name: Shipping Fluid

Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about protection against explosions and fires: No special measures required.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep receptacle tightly sealed.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Control parameters

Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

13048-33-4 hexamethylene diacrylate

WEEL Long-term value: 1 mg/m3

DSEN

Additional information: The lists that were valid during the creation were used as basis.

Exposure controls

Appropriate engineering controls No further data; see section 7.

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Date of issue: 08/08/2025 Version: 2.0 Reviewed on 08/04/2025

Product name: Shipping Fluid

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

Information on basic physical and chemical properties

General Information

Physical state Liquid

Color: According to product specification

Odor: Characteristic
Odor threshold: Not determined.
Melting point/Melting range: Undetermined.
Boiling point/Boiling range: Undetermined.
Flammability: Not applicable.

Explosion limits:

Lower:
Upper:
Not determined.
Not determined.

Flash point:
Not determined.
> 100 °C (> 212 °F)

Decomposition temperature:
Not determined.

PH-value:
Not determined.

Viscosity:

Kinematic: Not determined. **Dynamic:** Not determined.

Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

Partition coefficient (n-octanol/water): Not determined.

Vapor pressure at 50 °C (122 °F): 0 hPa

Vapor pressure:

Density:Not determined.Relative densityNot determined.Vapor densityNot determined.Particle characteristicsNot applicable.

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Date of issue: 08/08/2025 Version: 2.0 Reviewed on 08/04/2025

Product name: Shipping Fluid

Other information

Appearance: Form:

Liquid

Important information on protection of health and

environment, and on safety.

Ignition temperature: Product is not selfigniting.

Danger of explosion: Product does not present an explosion hazard.

Change in condition

Evaporation rate Not determined.

10 Stability and reactivity

Reactivity No further relevant information available.

Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Possibility of hazardous reactions No dangerous reactions known.

Conditions to avoid No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products: No dangerous decomposition products known.

*11 Toxicological information

Information on toxicological effects

Acute toxicity:

LD/LC50 values that are relevant for classification:

13048-33-4 hexamethylene diacrylate

Oral LD50 > 5,000 mg/kg (rat)

Dermal LD50 > 3,000 mg/kg (rab)

Primary irritant effect:

on the skin: Irritant to skin and mucous membranes.

on the eye: Irritating effect.

Sensitization: Sensitization possible through skin contact.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

Interactive effects No interactive effects between components are known.

Carcinogenic categories

IARC (International Agency for Research on Cancer)

100-41-4 ethylbenzene: 2B

127-19-5 N,N-dimethylacetamide: 2B

NTP (National Toxicology Program)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

Alternative sources for toxicological information

No non-standard sources for toxicological information where used.

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Date of issue: 08/08/2025 Version: 2.0 Reviewed on 08/04/2025

Product name: Shipping Fluid

12 Ecological information

Toxicity

Aquatic toxicity: No further relevant information available.

Persistence and degradability No further relevant information available. Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable. Other adverse effects Remark: Toxic for fish

Additional ecological information:

General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

13 Disposal considerations

Waste treatment methods

Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

14 Transport information

UN-Number

DOT not regulated UN3082 IMDG, IATA

UN proper shipping name

DOT not regulated

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, **IMDG**

N.O.S. (hexamethylene diacrylate, Neopentylglycol(PO)2 Diacrylate),

MARINE POLLUTANT

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, **IATA**

N.O.S. (hexamethylene diacrylate, Neopentylglycol(PO)2 Diacrylate)

Transport hazard class(es)

DOT

Class not regulated

IMDG, IATA



9 Miscellaneous dangerous substances and articles Class 9

Label

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Date of issue: 08/08/2025 Version: 2.0 Reviewed on 08/04/2025

Product name: Shipping Fluid

Packing group

DOT not regulated

IMDG, IATA III

Environmental hazards:

Marine pollutant: Symbol (fish and tree)
Special marking (IATA): Symbol (fish and tree)

Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

Transport/Additional information:

IMDG

Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

Special precautions for user Warning: Miscellaneous dangerous substances and articles

Hazard identification number (Kemler code): 90
EMS Number: F-A,S-F
Stowage Category A

UN "Model Regulation": UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE,

LIQUID, N.O.S. (HEXAMETHYLENE DIACRYLATE,

NEOPENTYLGLYCOL(PO)2 DIACRYLATE), 9, III

*15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

No further relevant information available.

SARA

Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

Hazardous Air Pollutants

100-41-4 ethylbenzene

Proposition 65

Chemicals known to cause cancer:

100-41-4 ethylbenzene

127-19-5 N,N-dimethylacetamide

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

127-19-5 N,N-dimethylacetamide

Chemicals known to cause developmental toxicity:

127-19-5 N,N-dimethylacetamide

Carcinogenic categories

EPA (Environmental Protection Agency)

100-41-4 ethylbenzene: D

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Date of issue: 08/08/2025 Version: 2.0 Reviewed on 08/04/2025

Product name: Shipping Fluid

TLV (Threshold Limit Value)

100-41-4 ethylbenzene: A3

127-19-5 N,N-dimethylacetamide: A4

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



Signal word Warning

Hazard-determining components of labeling:

hexamethylene diacrylate

Neopentylglycol(PO)2 Diacrylate

Hazard statements

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves / eye protection / face protection.

If on skin: Wash with plenty of water.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

Specific treatment (see on this label).

If eye irritation persists: Get medical advice/attention.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eve irritation.

Date of previous version 09/10/2021

Version number of previous version: 1.0

Date of preparation 08/08/2025

Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Date of issue: 08/08/2025 Reviewed on 08/04/2025 Version: 2.0

Product name: Shipping Fluid

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Skin irritation 2: Skin corrosion/irritation – Category 2

Eye irritation 2A: Serious eye damage/eye irritation - Category 2A

Sensitization - skin 1: Skin sensitisation - Category 1

^{*} Data compared to the previous version altered.