

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 11/20/2023

Version: 2.2

Reviewed on 11/20/2023

### 1 Identification

#### Product identifier

**Product name: XFLEXX Series: White**

**Article number:** ixF-w

**Application of the substance / the mixture:** Printing inks

#### Details of the supplier of the safety data sheet

Inkcups Now Corp  
310 Andover Street  
Danvers, MA 01923  
USA  
1-978-646-8980

#### Manufacturer/Supplier:

Inkcups Now Corp  
310 Andover Street  
Danvers, MA 01923 USA

**Information department:** [compliance@inkcups.com](mailto:compliance@inkcups.com)

**Emergency telephone number:** Verisk 3E US & Canada: +1 866 519 4752; Access Code: 335740

### \* 2 Hazard(s) identification

#### Classification of the substance or mixture

Acute Toxicity - Oral 4    H302 Harmful if swallowed.  
Skin Corrosion 1C        H314 Causes severe skin burns and eye damage.  
Eye Damage 1            H318 Causes serious eye damage.  
Sensitization - Skin 1    H317 May cause an allergic skin reaction.  
Toxic to Reproduction 1B H360 May damage fertility or the unborn child.

#### Label elements

**GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

#### Hazard pictograms



GHS05    GHS07    GHS08

**Signal word** Danger

#### Hazard-determining components of labeling:

Tetrahydrofurfuryl Acrylate  
2-Propenoic acid, 2-[2-(ethenyloxy)ethoxy]ethyl ester  
Dipropylene glycol diacrylate  
2-phenoxyethyl acrylate  
propylidynetrimethanol, propoxylated, esters with acrylic acid  
4,4'-isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid

#### Hazard statements

Harmful if swallowed.  
Causes severe skin burns and eye damage.  
May cause an allergic skin reaction.

# Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 11/20/2023

Version: 2.2

Reviewed on 11/20/2023

**Product name: XFLEXX Series: White**

May damage fertility or the unborn child.

### Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

## \* 3 Composition/information on ingredients

### Chemical characterization: Mixtures

**Description:** Mixture of the substances listed below with nonhazardous additions.

### Dangerous components:

2399-48-6 Tetrahydrofurfuryl Acrylate	25 - 50%
Toxic to Reproduction 1B, H360; Skin Corrosion 1C, H314; Eye Damage 1, H318; Acute Toxicity - Oral 4, H302; Sensitization - Skin 1, H317; Flammable Liquids 4, H227	
13463-67-7 titanium dioxide	≥ 10 - ≤ 25%
Carcinogenicity 2, H351	
86273-46-3 2-Propenoic acid, 2-[2-(ethenoxy)ethoxy]ethyl ester	≥ 10 - ≤ 25%
Acute Toxicity - Oral 4, H302; Sensitization - Skin 1, H317	
48145-04-6 2-phenoxyethyl acrylate	10 - 25%
Toxic to Reproduction 2, H361; Sensitization - Skin 1A, H317	
57472-68-1 Dipropylene glycol diacrylate	≥ 2.5 - ≤ 10%
Eye Damage 1, H318; Skin Irritation 2, H315; Sensitization - Skin 1, H317	
75980-60-8 Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	2.5 - 10%
Toxic to Reproduction 2, H361	
53879-54-2 propylidynetrimethanol, propoxylated, esters with acrylic acid	2.5 - 10%
Eye Irritation 2A, H319; Sensitization - Skin 1, H317	
55818-57-0 4,4'-isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid	≥ 0 - ≤ 2.5%
Sensitization - Skin 1, H317	

# Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 11/20/2023

Version: 2.2

Reviewed on 11/20/2023

---

**Product name: XFLEXX Series: White**

---

---

## 4 First-aid measures

### Description of first aid measures

**General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

**After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

**After skin contact:** Immediately wash with water and soap and rinse thoroughly.**After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.**After swallowing:**

Immediately call a doctor.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

**Most important symptoms and effects, both acute and delayed** No further relevant information available.**Indication of any immediate medical attention and special treatment needed**No further relevant information available.

---

---

## 5 Fire-fighting measures

### Extinguishing media

**Suitable extinguishing agents:** Use fire fighting measures that suit the environment.**Special hazards arising from the substance or mixture** No further relevant information available.**Advice for firefighters****Protective equipment:** No special measures required.

---

---

## 6 Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

**Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

**Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

**Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

---

---

## 7 Handling and storage

### Handling:

**Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

---

---

# Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 11/20/2023

Version: 2.2

Reviewed on 11/20/2023

**Product name: XFLEXX Series: White**

Prevent formation of aerosols.

**Information about protection against explosions and fires:** Keep respiratory protective device available.

**Conditions for safe storage, including any incompatibilities**

**Storage:**

**Requirements to be met by storerooms and receptacles:** No special requirements.

**Information about storage in one common storage facility:** Not required.

**Further information about storage conditions:** Keep receptacle tightly sealed.

**Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

**Additional information about design of technical systems:** No further data; see section 7.

**Control parameters**

**Components with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

**Additional information:** The lists that were valid during the creation were used as basis.

**Exposure controls**

**Personal protective equipment:**

**General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

**Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

**Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye protection:**



Tightly sealed goggles

# Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 11/20/2023

Version: 2.2

Reviewed on 11/20/2023

Product name: XFLEXX Series: White

## 9 Physical and chemical properties

### Information on basic physical and chemical properties

#### General Information

##### Appearance:

Form:	Liquid
Color:	White
Odor:	Characteristic
Odor threshold:	Not determined.

pH-value: Not determined.

#### Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.

Flash point: Not applicable.

Flammability (solid, gaseous): Not applicable.

Decomposition temperature: Not determined.

Ignition temperature: Product is not selfigniting.

Danger of explosion: Product does not present an explosion hazard.

#### Explosion limits:

Lower:	Not determined.
Upper:	Not determined.

Vapor pressure: Not determined.

Density: Not determined.

Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.

#### Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

Partition coefficient (n-octanol/water): Not determined.

#### Viscosity:

Dynamic:	Not determined.
Kinematic:	Not determined.

Other information: No further relevant information available.

## 10 Stability and reactivity

Reactivity: No further relevant information available.

#### Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Possibility of hazardous reactions: No dangerous reactions known.

Conditions to avoid: No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products: No dangerous decomposition products known.

# Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 11/20/2023

Version: 2.2

Reviewed on 11/20/2023

Product name: XFLEXX Series: White

## \* 11 Toxicological information

### Information on toxicological effects

#### Acute toxicity:

#### LD/LC50 values that are relevant for classification:

#### ATE (Acute Toxicity Estimate)

Oral LD50 1,472 - 1,482 mg/kg

#### 2399-48-6 Tetrahydrofurfuryl Acrylate

Oral LD50 928 mg/kg (rat)

#### 13463-67-7 titanium dioxide

Oral LD50 > 20,000 mg/kg (rat)

Dermal LD50 > 10,000 mg/kg (rabbit)

Inhalative LC50/4 h > 6.82 mg/l (rat)

#### 86273-46-3 2-Propenoic acid, 2-[2-(ethenyloxy)ethoxy]ethyl ester

Oral LD50 500 mg/kg (ATE)

#### 53879-54-2 propylidynetrimethanol, propoxylated, esters with acrylic acid

Oral LD50 > 2,000 mg/kg (rat)

#### Primary irritant effect:

**on the skin:** Strong caustic effect on skin and mucous membranes.

**on the eye:** Strong caustic effect.

**Sensitization:** Sensitization possible through skin contact.

#### Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

#### Carcinogenic categories

#### IARC (International Agency for Research on Cancer)

13463-67-7 titanium dioxide: 2B

15625-89-5 2,2-bis(acryloyloxymethyl)butyl acrylate: 2B

108-88-3 Toluene: 3

100-41-4 ethylbenzene: 2B

127-19-5 N,N-dimethylacetamide: 2B

#### NTP (National Toxicology Program)

None of the ingredients is listed.

#### OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## 12 Ecological information

### Toxicity

**Aquatic toxicity:** No further relevant information available.

**Persistence and degradability** No further relevant information available.

### Behavior in environmental systems:

**Bioaccumulative potential** No further relevant information available.

**Mobility in soil** No further relevant information available.

# Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 11/20/2023

Version: 2.2

Reviewed on 11/20/2023

**Product name: XFLEXX Series: White**

## Ecotoxicological effects:

**Remark:** Toxic for fish

## Additional ecological information:

### General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

## Results of PBT and vPvB assessment

**PBT:** Not applicable.

**vPvB:** Not applicable.

**Other adverse effects** No further relevant information available.

## 13 Disposal considerations

### Waste treatment methods

#### Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

### Uncleaned packagings:

**Recommendation:** Disposal must be made according to official regulations.

## \*14 Transport information

### UN-Number

**DOT** not regulated

**IMDG, IATA** UN3082

### UN proper shipping name

**DOT** not regulated

**IMDG** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Tetrahydrofurfuryl Acrylate, 2-phenoxyethyl acrylate), MARINE POLLUTANT

**IATA** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Tetrahydrofurfuryl Acrylate, 2-phenoxyethyl acrylate)

### Transport hazard class(es)

**DOT**

**Class** not regulated

### IMDG, IATA



**Class**

9 Miscellaneous dangerous substances and articles

**Label**

9

### Packing group

**DOT** not regulated

**IMDG, IATA** III

### Environmental hazards:

**Marine pollutant:** Symbol (fish and tree)

**Special marking (IATA):** Symbol (fish and tree)

**Safety Data Sheet**

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 11/20/2023

Version: 2.2

Reviewed on 11/20/2023

**Product name: XFLEXX Series: White****Special precautions for user** Warning: Miscellaneous dangerous substances and articles**Hazard identification number (Kemler code):** 90**EMS Number:** F-A,S-F**Stowage Category** A**Transport in bulk according to Annex II of****MARPOL73/78 and the IBC Code** Not applicable.**Transport/Additional information:****IMDG****Limited quantities (LQ)** 5L**Excepted quantities (EQ)** Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

**UN "Model Regulation":**UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE,  
LIQUID, N.O.S. (TETRAHYDROFURFURYL ACRYLATE, 2-  
PHENOXYETHYL ACRYLATE), 9, III**\*15 Regulatory information****Safety, health and environmental regulations/legislation specific for the substance or mixture****SARA****Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

**Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

**TSCA (Toxic Substances Control Act):**

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

13463-67-7 titanium dioxide: ACTIVE

86273-46-3 2-Propenoic acid, 2-[2-(ethenoxy)ethoxy]ethyl ester: ACTIVE

48145-04-6 2-phenoxyethyl acrylate: ACTIVE

57472-68-1 Dipropylene glycol diacrylate: ACTIVE

75980-60-8 Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide: ACTIVE

53879-54-2 propylidynetrimethanol, propoxylated, esters with acrylic acid: ACTIVE

55818-57-0 4,4'-isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid: ACTIVE

**Hazardous Air Pollutants**

67-56-1 methanol

108-88-3 Toluene

100-41-4 ethylbenzene

**Proposition 65****Chemicals known to cause cancer:**

13463-67-7 titanium dioxide

15625-89-5 2,2-bis(acryloyloxymethyl)butyl acrylate

100-41-4 ethylbenzene

127-19-5 N,N-dimethylacetamide

**Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.



# Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 11/20/2023

Version: 2.2

Reviewed on 11/20/2023

**Product name: XFLEXX Series: White**

## **Chemicals known to cause reproductive toxicity for males:**

127-19-5 N,N-dimethylacetamide

## **Chemicals known to cause developmental toxicity:**

67-56-1 methanol

108-88-3 Toluene

127-19-5 N,N-dimethylacetamide

## **Carcinogenic categories**

### **EPA (Environmental Protection Agency)**

110-82-7 cyclohexane: I

108-88-3 Toluene: II

100-41-4 ethylbenzene: D

### **TLV (Threshold Limit Value)**

13463-67-7 titanium dioxide: A4

108-88-3 Toluene: A4

100-41-4 ethylbenzene: A3

127-19-5 N,N-dimethylacetamide: A4

### **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7 titanium dioxide

**GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

### **Hazard pictograms**



GHS05

GHS07

GHS08

**Signal word** Danger

### **Hazard-determining components of labeling:**

Tetrahydrofurfuryl Acrylate

2-Propenoic acid, 2-[2-(ethenoxy)ethoxy]ethyl ester

Dipropylene glycol diacrylate

2-phenoxyethyl acrylate

propylidynetrimethanol, propoxylated, esters with acrylic acid

4,4'-isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid

### **Hazard statements**

Harmful if swallowed.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

May damage fertility or the unborn child.

### **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

# Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 11/20/2023

Version: 2.2

Reviewed on 11/20/2023

**Product name: XFLEXX Series: White**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

**Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### Relevant phrases

H227 Combustible liquid.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

H360 May damage fertility or the unborn child.

H361 Suspected of damaging fertility or the unborn child.

### Contact:

**Date of preparation / last revision** 11/20/2023

### Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety &amp; Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flammable Liquids 4: Flammable liquids – Category 4

Acute Toxicity - Oral 4: Acute toxicity – Category 4

Skin Corrosion 1C: Skin corrosion/irritation – Category 1C

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Damage 1: Serious eye damage/eye irritation – Category 1

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Sensitization - Skin 1: Skin sensitisation – Category 1

Sensitization - Skin 1A: Skin sensitisation – Category 1A

Carcinogenicity 2: Carcinogenicity – Category 2

Toxic to Reproduction 1B: Reproductive toxicity – Category 1B

Toxic to Reproduction 2: Reproductive toxicity – Category 2

\* **Data compared to the previous version altered.**